

TARAUD ET FILIERE POUR BOUTEILLE GAZ - DIN 477

DIN 477 - VG - 55° - 60° - A DROITE (RH) - GAUCHE (LH) - UTILISATION GENERALE




TAP EN SNIJPLAAT VOOR GASFLESSEN - DIN 477

DIN 477 - VG - 55° - 60° - RECHTS (RH) - LINKS (LH) - ALGEMEEN GEBRUIK

TAP AND DIE FOR THREADS FOR GAS CYLINDERS DIN 477

DIN 477 - VG - 55° - 60° - RIGHT HAND (RH) - LEFT HAND (LH) - GENERAL USE





	Pas	Cylindrique						
	Spood	Cilindrisch	HSS	HSS	HSS	HSS		
	TPI	Cylindrical	RH	LH	RH	LH		
			201D477..	201D477..LH	223D477..	223D477..LH		
W 19,30	14	55° CYL	1930					
W 20	14	55° CYL	2000	2000	2000	2000		
W 20,8	14	55° CYL				2080		
W 21,7	14	55° CYL	2170	2170	2170	2170		
W 21,8	14	55° CYL	2180	2180	2180	2180		
W 22,91	14	55° CYL	2291					
W 24,32	14	55° CYL	2432		2432			

	PAS	Conicité	NORME				
	SPOED	Coniciteit		HSS	HSS		
	TPI	Taper	NORM	DIN 374	ISO 529		
				201D477..	223D477..		
W 19,8	14	CON 12%	17E	1980	1980		
24,2	2,00	CON 10%		2420			
26	2,00	CON 10%		2600	2600		
W 28,8	14	CON 12%	25E	2880	2880		
W 31,3	14	CON 12%		3130	3130		
W 34	2,00	CON 12%		34200			
36,8	2,00	CON 12%		3680	3680		

TARAUD ET FILIERE POUR VALVES DE PNEUS DIN 7756




TAP EN SNIJPLAAT VOOR SCHROEFDRAAD VOOR BANDVENTIEL DIN 7756

TAP & DIE FOR VALVE THREAD DIN 7756

VG	Dimension			VG	Dimension		
	Afmeting	HSS	HSS		Afmeting	HSS	HSS
	Dimension	DIN 223			Dimension	DIN 223	
		201DVG..	223VG..			201DVG..	223VG..
VG 5	5,2 -36	05	05	VG 8	7,68 - 32	08	08
VG 5,2	5,2 - 24	052	052	VG 10	10,27 - 28	10	10
VG 6	5,98 -32	06	06	VG 12	12,17 - 26	12	12

TARAUD ET FILIERE POUR BECS DEBRULEURS GAZ

TAP EN SNIJPLAAT VOOR GASBRANDERS - TAPS EN DIES FOR GAS

Bec Gaz Gasbranders	Pas	INFO					
	Spood		200BGZ..	201DM..	223BGZ..		
	TPI						
8	28	CYL	08-28				
8,15	28	CYL			0815-28		
10,85	19	CYL		1085-19			
9,96	1,00	CON 10%		0996-100			
10	28	CYL			10-28		
11,15	19	CYL		1115-19			
13	28	CYL		13-28			